



# **A2L** PRO STARTER KIT



## **NMG12A**

3-1/8" DIAL,  
R454B/32/410A/22

With a robust brass body and needle valve, it ensures durability and efficiency. The large, color-coded dial and precision gauge ensure easy reading, while glow-in-the-dark elements, class 1.0 accuracy, hose holders, and a hanging hook enhance usability. Add extra protection with the optional rubber boot NMGB1 (Sold separately).



## **N2A4B**

3-1/8" DIAL  
ALUMINUM BODY  
R454B/32/410A/22

Featuring the latest ergonomic design for easy handling, high precision with Class 1.0 accuracy, and an impact-resistant body for outstanding protection. With quarter-turn ball valve handles and a folding hook design for portability. Plus, illuminating dials for added convenience.



## **NH5L**

5' LONG, 1/4"  
DIAMETER, 1/4"  
TO 1/4" FITTINGS

Designed for reverse threaded A2L refrigerant and recovery tanks, the NH5L model offers reliability with its leak-proof 8-sided crimp. With 800 psi working pressure and 4000 psi burst pressure, it ensures efficiency. Featuring 1/4" SAE fittings with a 45° bend and a universal, replaceable gasket, it's versatile.

# NAVAC

Empowering you to work smarter



NAVAC  
A2L COMPATIBLE  
PRODUCTS



# A2L

## PRO DELUXE KIT



### NRP6Di NRP8Di

The light-weight, inverter-driven, dual-stage vacuum pump delivers high-speed evacuation along with high ultimate vacuum. Vacuum measurement technology precisely measures the system pressure. A digital display provides a comprehensive view of the system's internal vacuum condition.



### NRDD

RECOVERY UNIT,  
DUAL CYLINDER,  
DC & DIGITAL  
DISPLAY

The NRDD recovery unit features a Brushless DC Motor making it lightweight and much more efficient, a large backlit display, twin cylinder design with 2-row oversized condenser, oil free compressor and self-purging functionality.



### N2A4B

3-1/8" DIAL  
ALUMINUM BODY  
R454B/32/410A/22

Featuring the latest ergonomic design for easy handling, high precision with Class 1.0 accuracy, and an impact-resistant body for outstanding protection. With quarter-turn ball valve handles and a folding hook design for portability. Plus, illuminating dials for added convenience.



### NH5L

5' LONG, 1/4"  
DIAMETER, 1/4"  
TO 1/4" FITTINGS

Designed for reverse threaded A2L refrigerant and recovery tanks, the NH5L model offers reliability with its leak-proof 8-sided crimp. With 800 psi working pressure and 4000 psi burst pressure, it ensures efficiency. Featuring 1/4" SAE fittings with a 45° bend and a universal, replaceable gasket, it's versatile.